

# DELUX 43/50/55/60



**ING. O. FIORENTINI S.p.A.**

“THE BEST IN FLOOR MACHINES”  
sales@ingfiorentini.it • www.ingfiorentini.it

**SEDE AMM. E STABILIMENTI**

50030 **PIANCALDOLI** (FI) - **Loc. ROMBOLA** - Via Piancaldoli, 1896 - Tel. +39 055.8173610 - Fax +39 055.817144  
50033 **PIETRAMALA** (FI) - Via Lame, 70/B - Tel. +39 055.813447 - Fax +39 055.813504  
40024 **CASTEL SAN PIETRO** (BO) - Via Cà Bianca, 231/C - Tel. +39 051.941743 - Fax +39 051.6942400

**FILIALI**

20132 **MILANO** - Via Palmanova, 211/A - Tel. +39 02.27207783 - 2564810 - Fax +39 02.2592779  
00012 **GUIDONIA MONTECELIO (ROMA)** - Via Pontecorvo, 20 - Tel. +39 0774.357184 - Fax +39 0774.353419



SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES	DELUX 43 B	DELUX 43 E	DELUX 43 BM	DELUX 50 B	DELUX 50 E	DELUX 50 BM
Larghezza utile di lavoro / Scrubbing width Largeur de nettoyage	430 mm	430 mm	430 mm	500 mm	500 mm	500 mm
Rendimento orario max. / Cleaning capacity up to Rendement jusqu'à	m <sup>2</sup> /h 1800	m <sup>2</sup> /h 1800	m <sup>2</sup> /h 1800	m <sup>2</sup> /h 2000	m <sup>2</sup> /h 2000	m <sup>2</sup> /h 2000
Autonomia di lavoro max. / Operating range Autonomie	2/3 h	/	3/4 h	3/4 h	/	3/4 h
Capacità serbatoio soluzione / Solution tank capacity Capacité réservoir solution	50 L	50 L	55 L	50 L	50 L	55 L
Capacità serbatoio recupero / Recovery tank capacity Capacité réservoir recuperation	45 L	45 L	53 L	45 L	45 L	53 L
Velocità di avanzamento avanti - dietro / Forward speed forward - rear Vitesse d'avancement avant - arrière	0 - 4 Km/h	0 - 4 Km/h	0 - 4 Km/h	0 - 4 Km/h	0 - 4 Km/h	0 - 4 Km/h
Pendenza superabile a pieno carico / Max. slope Pente max. surmontable	6 %	6 %	6 %	6 %	6 %	6 %
Depressione / Water lift Dépression	117 mBar	117 mBar	117 mBar	117 mBar	117 mBar	117 mBar
Pressione testata spazzole / Brush pressure Pression des brosses	20 - 40 Kg	20 - 40 Kg	20 - 40 Kg	20 - 40 Kg	20 - 40 Kg	20 - 40 Kg
Rumorosità / Noise level Bruit	72 dB	72 dB	72 dB	72 dB	72 dB	72 dB
<b>SPECIFICHE ALIMENTAZIONE / POWER SPECIFICATIONS DONNEES DE L'ALIMENTATION</b>						
Motore trazione / Traction motor Moteur traction	24v 100w	/	24v 100w	24v 100w	/	24v 100w
Motore di aspirazione / Vacuum motor Moteur d'aspiration	24v 550w	230v 550w	24v 550w	24v 550w	230v 550w	24v 550w
Motore spazzole / Brush motor Moteur des brosses	1x 24v 400w	1x 230v 550w	1x 24v 400w	1x 24v 400w	1x 230v 550w	1x 24v 400w
Alimentazione / Voltage Alimentation	24v 2x 12v 110A/h	230v	24v 2x 12v 157A/h	24v 2x 12v 110A/h	230v	24v 2x 12v 157A/h
<b>DIMENSIONI E PESI / DIMENSIONS &amp; WEIGHT DIMENSIONS ET POIDS</b>						
Misure: L x l x h / Measures: L x w x h Mesures: L x l x h	mm 1000 x 480 x 1060	mm 1000 x 480 x 1060	mm 1000 x 480 x 1060	mm 1000 x 550 x 1060	mm 1000 x 550 x 1060	mm 1000 x 550 x 1060
Numero diametro spazzola/e / Number of brushes and diameter Nombre et diamètre des brosses	1 x Ø 430 mm	1 x Ø 430 mm	1 x Ø 430 mm	1 x Ø 500 mm	1 x Ø 500 mm	1 x Ø 500 mm
Larghezza tergipavimento / Squeegee width Largeur du suceur	750 mm	750 mm	750 mm	750 mm	750 mm	750 mm
Peso macchina a vuoto (senza batteria/ acqua/ operatore) Weight of the machine (without batteries/ water/ operator) Poids de la machine (sans batteries/ eau/ opérateur)	85 Kg	80 Kg	90 Kg	85 Kg	80 Kg	90 Kg
Peso batterie (apx.) / Weight of the batteries (approx.) Poids des batteries (approx.)	2 x 26 Kg	/	2 x 35 Kg	2 x 26 Kg	/	2 x 35 Kg



SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES	DELUX 55B/1SP DELUX 55B/2SP	DELUX 60 B	DELUX 55 BR
Larghezza utile di lavoro / Scrubbing width Largeur de nettoyage	550 mm	600 mm	505 mm
Rendimento orario max. / Cleaning capacity up to Rendement jusqu'à	m <sup>2</sup> /h 2200	m <sup>2</sup> /h 2400	m <sup>2</sup> /h 2200
Autonomia di lavoro max. / Operating range Autonomie	3/4 h	3/4 h	3/4 h
Capacità serbatoio soluzione / Solution tank capacity Capacité réservoir solution	55 L	55 L	55 L
Capacità serbatoio recupero / Recovery tank capacity Capacité réservoir recuperation	53 L	53 L	53 L
Velocità di avanzamento avanti - dietro / Forward speed forward - rear Vitesse d'avancement avant - arrière	0 - 4 Km/h	0 - 4 Km/h	0 - 4 Km/h
Pendenza superabile a pieno carico / Max. slope Pente max. surmontable	6 %	6 %	6 %
Depressione / Water lift Dépression	117 mBar	117 mBar	117 mBar
Pressione testata spazzole / Brush pressure Pression des brosses	20 - 40 Kg	20 - 40 Kg	20 - 40 Kg
Rumorosità / Noise level Bruit	72 dB	72 dB	72 dB
<b>SPECIFICHE ALIMENTAZIONE / POWER SPECIFICATIONS DONNEES DE L'ALIMENTATION</b>			
Motore trazione / Traction motor Moteur traction	24v 130w	24v 130w	24v 130w
Motore di aspirazione / Vacuum motor Moteur d'aspiration	24v 550w	24v 550w	24v 550w
Motore spazzole / Brush motor Moteur des brosses	1x 24v 650w 2 x 24v 200w	1x 24v 650w	1x 24v 650w
Alimentazione / Voltage Alimentation	24v 2x 12v 157A/h	24v 2x 12v 157A/h	24v 2x 12v 157A/h
<b>DIMENSIONI E PESI / DIMENSIONS &amp; WEIGHT DIMENSIONS ET POIDS</b>			
Misure: L x l x h / Measures: L x w x h Mesures: L x l x h	mm 1350 x 595 x 1040	mm 1300 x 710 x 1040	mm 1160 x 610 x 1060
Numero diametro spazzole / Number of brushes and diameter Nombre et diamètre des brosses	1 x Ø 550 mm 2 x Ø 275 mm	2 x Ø 305 mm	n° 2 rulli n° 2 cylindr. br. n° 2 br. cylindr. Ø110 L: 505
Larghezza tergipavimento / Squeegee width Largeur du suceur	750 mm	850 mm	750 mm
Peso macchina a vuoto (senza batteria/ acqua/ operatore) Weight of the machine (without batteries/ water/ operator) Poids de la machine (sans batteries/ eau/ opérateur)	105 Kg	105 Kg	105 Kg
Peso batterie (apx.) / Weight of the batteries (approx.) Poids des batteries (approx.)	2 x 35 Kg	2 x 35 Kg	2 x 35 Kg

