

# MINUTE TRACTORS



**fiorentini**  


**ING. O. FIORENTINI S.p.A.**

“THE BEST IN FLOOR MACHINES”  
sales@ingfiorentini.it • www.ingfiorentini.it



**ING. O. FIORENTINI S.p.A.**

**SEDE AMM. E STABILIMENTI**

50030 PIANCALDOLI (FI) - Loc. ROMBOLA Via Piancaldoli, 1896

Tel. +39 055.8173610 - Fax +39 055.817144

50033 PIETRAMALA (FI) - Via Lame, 70/B

Tel. +39 055.813447 - Fax +39 055.813504

40024 CASTEL SAN PIETRO (BO) Via Cà Bianca, 231/C

Tel. +39 051.941743 - Fax +39 051.6942400

**FILIALI**


20132 MILANO - Via Palmanova, 211/A

Tel. +39 02.27207783 - 2564810 - Fax +39 02.2592779

00012 GUIDONIA MONTECELIO (ROMA) - Via Pontecorvo, 20

Tel. +39 0774.357184 - Fax +39 0774.353419

**Distributed by:**



<b>SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES</b>	<b>TX 05</b>	<b>TX 07</b>	<b>TX 020</b>	<b>TX 050</b>
Trazione (ant - post) / Mechanical driver (front - rear) Traction (avant - arriere)	POST. REAR ARRIERE	POST. REAR ARRIERE	POST. REAR ARRIERE	POST. REAR ARRIERE
Velocità di avanzamento / Forward speed Vitesse	Km/h 8	Km/h 11	Km/h 12	Km/h 12
Pendenza superabile senza carico / Max. slope (without load) Pente sans charge	% 10	% 10	% 10	% 14
Autonomia di lavoro / Operating range of empty machine Autonomie de travail	h 6	h 6	h 5,5	h 5,5
Freno di servizio / Service Breake Frein de service	mec.pedale Mechanical pedal ped mecanique	mec.pedale Mechanical pedal ped mecanique	idrau.pedale hydraulic pedal ped hydraulique	idrau.pedale hydraulic pedal ped hydraulique
Peso rimorchiabile in piano / Towage weight on flat ground Poids deremorquage en plan	Kg 500	Kg 500	Kg 2000	Kg 5000
Raggio minimo di sterzata / Turning radius Rayon de braquage minimum	mm 1200	mm 1200	mm 1650	mm 1750
<b>IMPIANTO ELETTRICO / ELETTRIC DATES ELECTRIQUE</b>				
Tensione alimentazione / Power Alimentation	v 24	v 24	v 24	v 36
Motore di trazione / Traction motor Moteur traction	24v 07 Kw 2500 rpm	24v 07 Kw 2500 rpm	36v 2Kw 2400 rpm	36v 4Kw 2400 rpm
Alimentazione / Voltage Alimentation	Ah in C20 2 x12 v 330 amp	Ah in C20 2 x12 v 330 amp	Ah in C20 4 x 6 v 330 amp	Ah in C20 6 x 6 v 330 amp
<b>DIMENSIONI E PESI / DIMENSION &amp; WEIGHT DIMENSIONS ET POIDS</b>				
Misure: L x l x h / Measures: L x w x h Mesures: L x l x h	mm 1280 x 702 x 1005	mm 1280 x 702 x 1005	mm 1640 x 875 x 1110	mm 1730 x 875 x 1110
Numero - diametro ruote / Number - diameter wheels Nombre - diamètre des roves	3 x Ø 300 mm	3 x Ø 300 mm	3 x Ø 400 mm	3 x Ø 400 mm
Peso macchina a vuoto / Weight of the machine Poids machine a vide	Kg 106	Kg 106	Kg 296	Kg 354

